



# PixelStor5012

## 2U, 12-Drive Award-Winning Storage System

### Datasheet

The award-winning PS5012 provides unified storage for forensic-grade video recording and AI analytics metadata storage. It is the first storage system which provides uninterrupted video surveillance recording while simultaneously providing metadata to analytic servers. The PS series of product is known for its patented surveillance-optimized cache technology that can scale the video recording to thousands of HD cameras without dropping a single frame of video.

**Patented advanced video caching** technology (VAN, FlowThrough, StreamAlign) enables no recording gaps while increasing read/write performance.

**Full redundancy** and **high availability** ensure video recording does not stop and is not lost due to any storage failures.

**Storage Consolidation** for NVR/DVRs significantly lowers purchase, CAPEX, and OPEX costs.

**Storage monitoring tools** including BusyPlot, Proactive drive-cloning, performance and disk monitoring, and ZM (Zero Maintenance) technology to ensure the best system performance with no loss of video frames.

**Effortless installation,** management and administration.

### Features

- Up to 1.8 PB in just 7U (with PS392 expansion)
- Fully Hot-Swappable Chassis
- 5-yr Warranty

### Applications

- High-Performance Megapixel Cameras
- Very Large Video Surveillance Installations
- Analytics Metadata Storage

Copyright © 2022 Rasiliient Systems, Inc. Specifications are subject to change without notice

### For more information contact:

**Tel:** +1.408.730.2568 | **Toll Free:** +1.888.902.8981 | **Website:** www.rasiliient.com | **Sales:** sales@rasiliient.com | **Technical Support:** techsupport@rasiliient.com

## Specifications

<b>CPU</b>	Intel Ivy Bridge
<b>Controller</b>	Dual Redundant
<b>RAM</b>	Up to 16GB ECC DDR3 1600Mhz per Controller
<b>Networking</b>	5x GbE (10GbE Upgrade Available)
<b>Input/Output</b>	2x USB 2.0, Serial COM, SAS
<b>Max Storage</b>	Up to 216TB, Expandable with PS312e2 or PS392e
<b>RAID</b>	1, 5, 6, 10, 50, 60
<b>Power Loss Protection</b>	72 hours battery-backed memory
<b>Dimensions (W x D x H)</b>	17.6" x 23.63" x 3.5" / 446 x 600 x 88 mm
<b>Weight</b>	Max 80 Lbs / 36 Kgs
<b>Power Supply</b>	1+1 Redundant 600W 89-264V AC 47-63Hz
<b>Operating Temperature</b>	10 - 35 °C



\* Configuration of product may differ based on options

Copyright © 2022 Rasilient Systems, Inc. Specifications are subject to change without notice

### For more information contact:

**Tel:** +1.408.730.2568 | **Toll Free:** +1.888.902.8981 | **Website:** [www.rasilient.com](http://www.rasilient.com) | **Sales:** [sales@rasilient.com](mailto:sales@rasilient.com) | **Technical Support:** [techsupport@rasilient.com](mailto:techsupport@rasilient.com)